



丹阳市恩可玻璃纤维织造有限公司

Danyang NQ Glass Fiber Weaving Co., Ltd

地址：江苏。丹阳访仙镇

Add: Fangxian Town, Danyang City, Jiangsu province, China

Tel: 0086-511-86462550 Fax: 0086-511-86461999 [Http://www.nq-fiberglass.com](http://www.nq-fiberglass.com)

※Technical Specification of fiberglass mesh tape:

Style - CET60--9x9

Tensile Strength - N/50mm

Weight (g/m²) - 60±5%

Finish - Corrosion resistant and contact adhesive

Ignition loss - 18% +/- 10% or to customer requirements

Weave - Leno

Testing - ASTM D579

Width - 25, 35, 50, 75, 100, 150, 200, 300 and 1000mm

Roll Length - 20, 45, 50, 70, 75, 90, 150 meters or according to requirements

Packaging:

By shrink film each roll+catons; Or by PE bags each roll+cartons;

Technical Parameter:

产品规格:								
Mesh size	质量 Gram weight	用纱 Fiberglass Yarn		抗拉强度(N) Tensile strength		密度 Density		覆胶量 (%) Coating
		经纱 Warp	纬纱 Weft	经纱 Warp	纬纱 Weft	经纱	纬纱	
9x9	60g/m ²	12.5×1×2	80	≥360N	≥600 N	8±0.5	8±0.5	≥28